



# AND-BTN-KIT-1

## AND Button Kit

### Overview

Enable two-way communication with the push of a button by connecting the AND Button Kit (AND-BTN-KIT-1) to a compatible IP device.

When connected to a compatible IP device, the AND-BTN-KIT-1 easily integrates with VoIP phone systems, approved 3rd party software, and includes ClockWise Campus software with purchase.

### Description



#### AUDIO FUNCTIONALITY

Intercom, page, or all-call. Trigger pre-programmed text, or privacy mode.



#### DUAL COMMANDS

Programmable button modes push/release or push/hold accommodate up to two extensions or phone numbers.



#### SIP INTEGRATION

Enable SIP calls. Dial out pre-programmed internal extensions and external phone numbers.



#### NOTIFICATION

Trigger alerts that activate other devices, such as a strobe or electronic lock.




#### SOFTWARE

ClockWise Campus software included. Compatible with approved third-party software.


Solutions	Additional Features	Compatible IP Devices	Accessories
<ul style="list-style-type: none"> <li>• Paging</li> <li>• Intercom</li> <li>• Emergency notification</li> </ul>	<ul style="list-style-type: none"> <li>• Built-in web server</li> </ul>	<ul style="list-style-type: none"> <li>• <b>HD IP Display</b> <ul style="list-style-type: none"> <li>• IPCSHD-MB</li> </ul> </li> <li>• <b>IP Speaker with HD Display</b> <ul style="list-style-type: none"> <li>• IPSWDHD-MW</li> </ul> </li> <li>• <b>Large Signboard</b> <ul style="list-style-type: none"> <li>• IPSIGNL-RWB</li> </ul> </li> <li>• <b>Zone Controller</b> <ul style="list-style-type: none"> <li>• ZONEC2</li> </ul> </li> </ul>	<ul style="list-style-type: none"> <li>• Standard junction box required for mounting (not included).</li> </ul>

## Dimensions

(Dimensions are subject to change)



Front



Side

## Specifications

Due to continual product development, specifications are subject to change without notice.

Faceplate Material	16-gauge brushed stainless steel
Electrical Life	200,000 cycles
Rating	2a@48V DC
Switch Function	Momentary ON
Operating Temperature	-4° TO 131° F (-20° TO 50° C)
Circuit	SPST
Installation Depth	1" (25.4 mm)
Dimensions	Plate: 2.75" W 4.5" H
Weight	3.8 oz
Warranty	2 Year Limited

