



# BTN-KIT-MIC-ND

Call Button Kit with Microphone

## Overview

Enable two-way communication with the push of a button by connecting the Call Button Kit with Microphone (BTN-KIT-MIC-ND) to a compatible IP device.

When connected to a compatible IP device, the BTN-KIT-MIC-ND easily integrates with VoIP phone systems, approved 3rd party software, and includes ClockWise Campus software with purchase.

## Description



### AUDIO FUNCTIONALITY

Intercom, page, or all-call. Trigger pre-programmed text, or privacy mode.



### MICROPHONE

Hands-free two-way intercom.



### DUAL COMMANDS

Programmable button modes push/release or push/hold accommodate up to two extensions or phone numbers.



### SIP INTEGRATION

SIP-enabled. Dials a preset phone number to play a pre-recorded message.



### NOTIFICATION

Trigger alerts that activate other devices, such as a strobe or electronic lock.



### SOFTWARE

ClockWise Campus software included. Compatible with approved third-party software.




### LED BUTTON

Illuminates when microphone is active.


Solutions	Additional Features	Compatible IP Devices		Accessories
<ul style="list-style-type: none"> <li>Paging</li> <li>Intercom</li> <li>Emergency notification</li> </ul>	<ul style="list-style-type: none"> <li>Built-in web server</li> </ul>	<b>Round Ceiling IP Speaker</b> <ul style="list-style-type: none"> <li>IPSCM-RMe</li> </ul>	<b>IP Speaker with HD Display</b> <ul style="list-style-type: none"> <li>IPSWDHD-MW</li> </ul>	<ul style="list-style-type: none"> <li>Standard junction box required for mounting.</li> <li>Requires RJ25 cable (6P6C)</li> </ul>
		<b>Square Ceiling Tile IP Speaker</b> <ul style="list-style-type: none"> <li>IPSCM</li> </ul>	<b>Double-Sided IP Display</b> <ul style="list-style-type: none"> <li>IPCDS-RWB-U</li> </ul>	
		<b>Surface/Flush Mount IP Speaker</b> <ul style="list-style-type: none"> <li>IPSW-SM / FM</li> </ul>	<b>IP Speaker with Display</b> <ul style="list-style-type: none"> <li>IPSWD-RWB</li> </ul>	
		<b>HD IP Display</b> <ul style="list-style-type: none"> <li>IPCSDH-MB</li> </ul>	<b>Small IP Display</b> <ul style="list-style-type: none"> <li>IPCSS-RWB / MB</li> </ul>	
			<b>Large IP Display</b> <ul style="list-style-type: none"> <li>IPCSL-RWB</li> </ul>	

## Dimensions

(Dimensions are subject to change)



Front



Side

## Specifications

Due to continual product development, specifications are subject to change without notice.

Faceplate Material	16-gauge brushed stainless steel
Electrical Life	200,000 cycles
Power Connection	RJ25 cable (6P6C)
Switch Function	Momentary ON
Operating Temperature	-4° TO 131° F (-20° TO 50° C)
Circuit	SPST
Max Distance from Endpoint	Up to 25ft
Installation Depth	1" (25.4 mm)
Dimensions	2.75" W x 4.5" H
Weight	4 oz
Warranty	2 Year Limited

