ADVANCED
NETWORK DEVICES

IPCSL-RWB

Large IP Display

Overview

Notify large audiences in auditoriums, cafeterias, or multi-purposes spaces with the PoE Large IP Display. Display alerts, countdown timers, and announcements on the large 17"x5" display using multi-colored text, LED flashers, and 8 inch speaker to be seen and heard throughout the large space.

The IPCSL-RWB easily integrates with VoIP phone systems, approved 3rd party software, and includes ClockWise Campus software with purchase.

Description

DISPLAY
Multi-color LED scrolling text and pixel graphics. 1-line or 2-line display.

MICROPHONE
Hands-free two-way intercom.

FLASHER
One red, one white, one blue LED flasher. Individually controlled.

AUDIO
8" high-efficiency speaker audio coverage up to 600ft^2.

PERIPHERAL INTEGRATION
Connect a strobe, motion sensor, electronic lock, call button, etc.

SOFTWARE
ClockWise Campus software included. Compatible with approved third-party software.

SIP INTEGRATION
SIP-enabled. Easily interfaces with VoIP / SIP phone systems.

LIGHT SENSOR
Auto-dimming display.

Solutions

- Paging
- Intercom
- Bell scheduling
- Code alerts
- Emergency notification
- Access control
- Security monitoring
- Music streaming

Additional Features

- Built-in web server
- Full multicast and broadcast support
- Requires Cat5 or Cat6 cable
- Back enclosure is included
- Atomic time

Compatible Peripherals

Strobe Kit
- AND-STROBE-KIT-1

Call Button Kit with Mic
- BTN-KIT-MIC-ND

Dimensions

(Dimensions are subject to change)

Front

Back

Side

Top

Specifications

Due to continual product development, specifications are subject to change without notice.

Power Input	PoE (IEEE802.3af) 15.4 W or PoE+ (IEEE802.3at) 30.0 W
Ethernet I/F	10/100 Mbps
Speaker Size	8"
Audio Power	8 W / 16 W
Frequency Response	60 Hz - 17 kHz
Audio Payload Types	G711, A-law and μ-law
Average Sensitivity	95dB, 1W / 1 M
Supported Protocols	SIP, IPv4, IPv6, 802.1X, HTTP, SLP, TFTP, NTP, SNMPV1 & SNMPV2c, DHCP, IGMP, ICMP, TCP/IP, LLDP-MED, UDP, MDNS & MDNS-SD
General Purpose Interface	2 GPI: 1 via RJ-11, 1 via Cable Harness 1 GPO 17.5 VDC
Operating Temperature	14˚ TO 122˚ F (-10˚ TO 50˚ C)
Dimensions	28.14" W x 9.2" H x 3.88" D
Weight	15 lbs (6.8 kg)
Warranty	2 Year Limited